

SAFETY DATA SHEET

ENGINE ENAMEL PRIMERS

Infosafe No.: LPV66
Issued Date: 29/02/2016
Issued by: SPECO THOMAS PTY. LTD.

1. IDENTIFICATION

GHS Product Identifier

ENGINE ENAMEL PRIMERS

Product Code

SP147, SP148

Company Name

SPECO THOMAS PTY. LTD. (ABN 58 005 669 269)

Address

1B LEVANSWELL ROAD MOORABBIN
VIC 3189 Australia

Telephone/Fax Number

Tel: 03 95557244

Fax: 03 95532841

Emergency phone number

131 126

Recommended use of the chemical and restrictions on use

Aerosol coating

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Eye Damage/Irritation: Category 2A

Flammable Aerosol: Category 1

Skin Corrosion/Irritation: Category 2

STOT Repeated Exposure: Category 1

STOT Repeated Exposure: Category 2

STOT Single Exposure: Category 3 (narcotic)

Toxic to Reproduction: Category 1A

Signal Word (s)

DANGER

Hazard Statement (s)

H222 Extremely flammable aerosol.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child .

H372 Causes damage to organs central nervous system through prolonged or repeated exposure .

H373 May cause damage to organs through prolonged or repeated exposure .

Pictogram (s)

Flame, Exclamation mark, Health hazard

**Precautionary statement – Prevention**

- P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P264 Wash contaminated skin thoroughly after handling
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P314 Get medical advice/attention if you feel unwell.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P362 Take off contaminated clothing and wash before reuse.

Precautionary statement – Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Precautionary statement – Disposal

- P501 Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS**Information on Composition**

The classification as a carcinogen or mutagen does not apply since the substance contains less than 0.1% w/w 1,3 butadiene (EINECS no 203-450-8).

Ingredients

Name	CAS	Proportion
Petroleum gases, liquefied	68476-85-7	30-60 %
Acetone	67-64-1	30-60 %
Solvent naphtha (petroleum), light aliphatic	64742-89-8	10-30 %
Toluene	108-88-3	1-10 %
Solvent naphtha (petroleum) medium aliphatic	64742-88-7	1-10 %
Ingredients determined not to be hazardous.		Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion

Unlikely due to form of product. If ingestion occurs, do not induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use carbon dioxide, dry chemical, foam, water fog or water mist.

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes including oxides of nitrogen, carbon monoxide and carbon dioxide and unidentified organic compounds.

Specific Hazards Arising From The Chemical

Vapours are heavier than air and will 'travel' to low-level areas e.g. sumps, drains, etc. Aerosol containers may explode and may become a projectile in a fire.

Contents under pressure - cans can explode in a fire. This product is extremely flammable. Keep containers and fire-exposed surfaces cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

2YE

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Extinguish or remove all sources of ignition and stop leak if safe to do so. Wear appropriate personal protective equipment and clothing to prevent exposure. Evacuate all unprotected personnel. Water spray or fog may be used to disperse/absorb vapour if any. Place inert, Non-combustible absorbent material onto spillage. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Collect residues and seal in labelled drums for disposal. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations. Dispose of waste according to applicable local and national regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

EXTREMELY FLAMMABLE. VAPOUR OR GAS REDUCES OXYGEN FOR BREATHING. IN CONFINED SPACES MAY CAUSE ASPHYXIATION. Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. DO NOT store or use in confined spaces. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Build up of mists or vapours in the atmosphere must be prevented. Do NOT cut or heat containers as they may contain hazardous residues. Do not smoke. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Avoid exposure. Do not handle until all safety precautions have been read and understood. It is recommended that pregnant or breastfeeding women should not handle this product unless adequate exposure protection can be assured at all times. Female personnel planning pregnancy should be made aware of the potential risks.

Conditions for safe storage, including any incompatibilities

Store in a cool (<49°C), dry, well ventilated area away from sources of ignition, oxidising agents, foodstuffs, clothing and out of direct sunlight. Do not expose can to temperatures exceeding 50°C. Protect containers against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Do NOT pressurise, cut or heat aerosol containers. Content is under pressure and can explode violently. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS 2278.1 Non-refillable metal aerosol dispensers of capacity 50 mL to 1000 mL inclusive.

Storage Temperatures

<49°C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Acetone

TWA: 500ppm, 1185 mg/m³

STEL: 1000ppm, 2375mg/m³

Toluene

TWA: 50 ppm, 191 mg/m³

STEL: 150 ppm, 574 mg/m³

NOTE: Sk

Petroleum gases, liquefied

TWA: 1000 ppm, 1800 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-

hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

Biological Limit Values

Name: Acetone

Determinant: Acetone

Specimen: Urine

Value: 50 mg/L

Sampling time: end of shift.

Name: Toluene

Determinant: toluene in urine

Value: 0.03mg/l

Sampling time: end of shift.

Name: Toluene

Determinant: toluene in blood

Value: 0.02mg/l

Sampling time: prior to last shift of workweek

Name: Toluene

Determinant: o-Cresol in urine

Value: 0.3mg/g creatinine

Sampling time: end of shift.

Source: American Conference of Industrial Hygienists (ACGIH)

Other Exposure Information

Petroleum gases, liquefied is asphyxiant gases which when present in an atmosphere in high concentration, lead to reduction of oxygen concentration by displacement or dilution. It is not appropriate to recommend an exposure standard for each simple asphyxiant, rather it should be required that a sufficient oxygen concentration be maintained.

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements. Refer to AS 2865 Australian Standard Safe working in a confined space, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour/mist filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as neoprene gloves. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective clothing should be worn e.g. cotton overalls buttoned at neck and wrist. When large quantities are handled the use of chemical resistant apron and safety boots is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Aerosol	Appearance	Aerosol paint
Colour	Not available	Odour	Solvent odour
Decomposition Temperature	Not available	Melting Point	Not available
Boiling Point	-25 to 199°C	Solubility in Water	Not available
Specific Gravity	Not available	pH	Not applicable
Vapour Pressure	52 +/- 5 psig at 21°C	Vapour Density (Air=1)	Heavier than air.
Evaporation Rate	Faster than ether	Odour Threshold	Not available
Viscosity	Not available	Partition Coefficient: n-octanol/water	Not available
Flash Point	Propellant below -18°C	Flammability	Extremely flammable.
Auto-Ignition Temperature	Not available	Flammable Limits - Lower	0.9%
Flammable Limits - Upper	10.6%	Melting/Freezing Point	Not available

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of storage and handling.

Reactivity and Stability

Reacts with incompatible materials

Conditions to Avoid

Heat, direct sunlight, flames and other sources of ignition.

Incompatible materials

Strong oxidising agents, strong acids and bases, selected amines.

Hazardous Decomposition Products

Thermal decomposition and combustion produce noxious fumes containing carbon monoxide, carbon dioxide and unidentified organic compounds.

Possibility of hazardous reactions

Reacts with incompatibles.

Hazardous Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material.

Ingestion

Unlikely due to form of product. If ingestion occurs, may cause lung damage if swallowed. Subsequent to ingestion or vomiting, small amounts of liquid aspirated into the respiratory system may cause severe pulmonary injury that may lead to death. May also cause irritation to the gastrointestinal system. Symptoms may include nausea, vomiting, diarrhoea and abdominal pain.

Inhalation

May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting.

Petroleum gases, liquefied is asphyxiant gases which when present in an atmosphere in high concentration, leads to reduction of oxygen concentration by displacement or dilution. Symptoms include decreased visual acuity, decreased coordination and judgment, headache, dizziness, confusion, drowsiness, fatigue, shortness of breath, muscular weakness, convulsions,

unconsciousness, coma and eventually death.

Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

Toluene is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

May damage fertility or the unborn child. Classified as a Known or presumed human reproductive or developmental toxicant.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. Causes damage to organs central nervous system through prolonged or repeated exposure .

Aspiration Hazard

Not expected to be an aspiration hazard.

Other Information

Prolonged or repeated skin contact may cause defatting leading to drying and cracking of skin and dermatitis. Prolonged inhalation may cause central nervous system depression with symptoms including dizziness, drowsiness, nausea and headaches. Chronic exposure may have adverse effects on the central nervous system, liver and kidneys.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No ecological data are available for this material.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Dispose of waste according to applicable local and national regulations. Do not pierce, burn, cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Empty the container completely before disposal. Contaminated containers must not be treated as household waste. Advise flammable nature.

14. TRANSPORT INFORMATION

Transport Information

Road and Rail Transport (ADG Code):

This material is classified as Dangerous Goods Division 2.1 Flammable Gases

Division 2.1 Dangerous Goods are incompatible in a placard load with any of the following:

- Class 1: Explosives
- Division 2.2 Non-flammable, Non toxic gas that have a subsidiary risk 5.1 except when all are packed in cylinders or pressure drums not exceeding 500L capacity.
- Class 3: Flammable Liquids, if both the Division 2.1 and Class 3 dangerous goods are in tanks or other receptacles with a capacity individually exceeding 500L.
- Division 4.1: Flammable Solids
- Division 4.2: Spontaneously combustible substances
- Division 4.3: Dangerous when wet substances
- Division 5.1: Oxidising substances
- Division 5.2: Organic peroxides
- Class 7: Radioactive materials unless specifically

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Proper Shipping Name: AEROSOLS

UN-No: 1950

Division: 2.1

EmS: F-D,S-U

Special Provisions: 63, 190, 277, 327, 344, 959

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Proper Shipping Name: AEROSOLS, FLAMMABLE

UN-No: 1950

Division: 2.1

Label: Flammable gas

Packaging Instructions (cargo only): 203

Packaging Instructions (passenger & cargo): 203

Special Provisions: A145, A167, A802

U.N. Number

1950

UN proper shipping name

AEROSOLS

Transport hazard class(es)

2.1

Hazchem Code

2YE

Special Precautions for User

Not available

EPG Number

2D1

IERG Number

49

IMDG Marine pollutant

No

Transport in Bulk

Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule

S5

Hazard Category

Harmful,Irritant,Extremely Flammable

16. OTHER INFORMATION

Date of preparation or last revision of SDS

MSDS Reviewed: February 2016

Supersedes: February 2011

References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants, Safe work Australia.

American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of classification and labelling of chem

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.