

SAFETY DATA SHEET

CALIPER CLEANER

Infosafe No.: LPZ90
ISSUED Date: 08/09/2015
ISSUED BY SPECO THOMAS PTY. LTD.

1. IDENTIFICATION

GHS Product Identifier

CALIPER CLEANER

Product Code

SP700

Company Name

SPECO THOMAS PTY. LTD. (ABN 58 005 669 269)

Address

1B LEVANSWELL ROAD MOORABBIN
VIC 3189 Australia

Telephone/Fax Number

Tel: 03 95557244

Fax: 03 95532841

Emergency phone number

131 126

Recommended use of the chemical and restrictions on use

Cleaning calipers.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

GHS Classification:

Flammable Aerosol: Category 1

Skin corrosion/irritation category 2

Eye damage/irritation 2A

STOT repeated exposure category 2

STOT single exposure category 3 - narcotic

Toxic to reproduction 2

Hazardous to the aquatic environment - acute hazard category 2

Hazardous to the aquatic environment - long term hazard category 2

Signal Word (s)

DANGER

Hazard Statement (s)

H222 Extremely flammable aerosol.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Pictogram (s)

Exclamation mark, Flame, Environment, Health Hazard



Precautionary statement – Prevention

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash contaminated skin thoroughly after handling
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Use personal protective equipment as required.

Precautionary statement – Response

P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P308+P313 IF exposed or concerned: Get medical advice/ attention.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P391 Collect spillage.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362 Take off contaminated clothing and wash before re-use.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P332+P313 If skin irritation occurs: Get medical advice/ attention.

Precautionary statement – Storage

P405 Store locked up.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Precautionary statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
Acetone	67-64-1	60-100 %
Toluene	108-88-3	10-<30 %
Heptane	142-82-5	<10 %
Carbon dioxide	124-38-9	<10 %
Ingredients determined not to be hazardous	Not applicable	Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion

Unlikely due to form of product. However, if ingested, do not induce vomiting. Wash out mouth thoroughly with water. If symptoms develop seek medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use carbon dioxide, dry chemical or foam.

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific Hazards Arising From The Chemical

Contents under pressure - cans can explode in a fire. This product is extremely flammable. Keep containers and fire-exposed surfaces cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

2YE

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Extinguish or remove all sources of ignition and stop leak if safe to do so. Wear appropriate personal protective equipment and clothing to prevent exposure. Evacuate all unprotected personnel. Water spray or fog may be used to disperse/absorb vapour if any. Place inert, Non-combustible absorbent material onto spillage. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Collect residues and seal in labelled drums for disposal. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations. Dispose of waste according to applicable local and national regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

EXTREMELY FLAMMABLE. VAPOUR OR GAS REDUCES OXYGEN FOR BREATHING. IN CONFINED SPACES MAY CAUSE ASPHYXIATION. Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. DO NOT store or use in confined spaces. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Build up of mists or vapours in the atmosphere must be prevented. Do NOT cut or heat containers as they may contain hazardous residues. Do not smoke. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Avoid exposure. Do not handle until all safety precautions have been read and understood. It is recommended that pregnant or breastfeeding women should not handle this product unless adequate exposure protection can be assured at all times. Female personnel planning pregnancy should be made aware of the potential risks.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area away from sources of ignition, oxidising agents, foodstuffs, clothing and out of direct sunlight. Do not expose can to temperatures exceeding 50°C. Protect containers against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Do NOT pressurise, cut or heat aerosol containers. Content is under pressure and can explode violently. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS 2278.1 Non-refillable metal aerosol dispensers of capacity 50 mL to 1000 mL inclusive.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure value assigned for this material by Safe Work, Australia. However, the available exposure limits for ingredients are listed below:

Substance	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
Heptane	400	1640	500	2050	-
Acetone	500	1185	1000	2375	-
Toluene	50	191	150	574	Sk
Carbon dioxide	5000	9000	30000	54000	-

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

Biological Limit Values

Name: Acetone

Determinant: Acetone in urine

BEI®: 50mg/l

Sampling time: end of shift.

Name: Toluene

Determinant: toluene in urine

BEI®: 0.03mg/l

Sampling time: end of shift.

Determinant: toluene in blood:

BEI®: 0.02mg/l

Sampling time: prior to last shift of workweek

Determinant: o-Cresol in urine*

BEI®: 0.3mg/g creatinine

Sampling time: end of shift.

* with hydrolysis

Source : American Conference of Industrial Hygienists (ACGIH)

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 2865 Australian Standard Safe working in a confined space, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Other Information

Carbon dioxide is asphyxiant gas which when presents in an atmosphere in high concentration, lead to reduction of oxygen concentration by displacement or dilution. It is not appropriate to recommend an exposure standard for each simple asphyxiant, rather it should be required that a sufficient oxygen concentration be maintained.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Appearance	Aerosol can	Colour	Not available
Odour	Not available	Decomposition Temperature	Not available
Melting Point	Not available	Boiling Point	-18°C
Solubility in Water	Insoluble	Specific Gravity	0.81
pH	Not available	Vapour Pressure	Not available
Vapour Density (Air=1)	Heavier than air	Evaporation Rate	Faster than ether.
Odour Threshold	Not available	Viscosity	Not available
Partition Coefficient: n-octanol/water	Not available	Flash Point	<-17°C (Closed-cup)
Flammability	Extremely flammable	Auto-Ignition Temperature	Not available
Flammable Limits - Lower	1.0%	Flammable Limits - Upper	12.8%

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of storage and handling.

Conditions to Avoid

Extremes of temperature, heat, direct sunlight, flames and other sources of ignition.

Incompatible materials

Strong oxidizing agents.

Hazardous Decomposition Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Possibility of hazardous reactions

Will react with incompatibles.

Hazardous Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material.

Ingestion

Unlikely due to form of product.

Inhalation

May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting.

Carbon dioxide is an asphyxiant gas which when presents in an atmosphere in high concentration, leads to reduction of oxygen concentration by displacement or dilution. Symptoms include decreased visual acuity, decreased coordination and judgment, headache, dizziness, confusion, drowsiness, fatigue, shortness of breath, muscular weakness, convulsions, unconsciousness, coma and eventually death.

Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

Toluene is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

Suspected of damaging fertility or the unborn child. Classified as a suspected human reproductive or developmental toxicant.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard

Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Persistence and degradability

Not available

Mobility

Insoluble in water.

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Dispose of waste according to applicable local and national regulations. Do not pierce, burn, cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Empty the container completely before disposal. Contaminated containers must not be treated as household waste. Advise flammable nature.

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

14. TRANSPORT INFORMATION

Transport Information

Road and Rail Transport (ADG Code):

This material is classified as Dangerous Goods Division 2.1 Flammable Gases

Division 2.1 Dangerous Goods are incompatible in a placard load with any of the following:

- Class 1: Explosives
- Division 2.2 Non-flammable, Non toxic gas that have a subsidiary risk 5.1 except when all are packed in cylinders or pressure drums not exceeding 500L capacity.
- Class 3: Flammable Liquids, if both the Division 2.1 and Class 3 dangerous goods are in tanks or other receptacles with a capacity individually exceeding 500L.
- Division 4.1: Flammable Solids
- Division 4.2: Spontaneously combustible substances
- Division 4.3: Dangerous when wet substances
- Division 5.1: Oxidising substances
- Division 5.2: Organic peroxides
- Class 7: Radioactive materials unless specifically exempted

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Proper Shipping Name: AEROSOLS (Heptane) MARINE POLLUTANT

UN-No: 1950

Division: 2.1

EmS: F-D,S-U

Special Provisions: 63, 190, 277, 327, 344, 959

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations

for transport by air.
Proper Shipping Name: Aerosols,flammable
UN-No: 1950
Division: 2.1
Label: Flammable gas
Packaging Instructions (cargo only): 203
Packaging Instructions (passenger & cargo): 203
Special Provisions: A145, A167, A802

U.N. Number

1950

UN proper shipping name

AEROSOLS

Transport hazard class(es)

2.1

Hazchem Code

2YE

Special Precautions for User

Not available

EPG Number

2D1

IERG Number

49

IMDG Marine pollutant

Yes

Transport in Bulk

Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule

S5

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS Reviewed: September 2015 Supersedes: July 2010

References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants, Safe work Australia.

American Conference of Industrial Hygienists (ACGIH)

Globally Harmonised System of classification and labelling of chemicals.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical

Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.